


GoldStar



	1460 PLUS VGA - COLOR	1460 SSI MPR II, VGA - COLOR	1465 SSI MPR II, MULTI-SCAN
Diagonal Size	14"	14"	14"
Type	Multimode	Multimode/Low Radiation	Multimode/ Low Radiation
Tube Surface	Non-Glare	Non-Glare	Non-Glare
Display Area (H x V mm)	245 x 185	245 x 185	250 x 183
Display Resolution	IBM* 8514/A 1024 x 768 EVGA 800 x 600 VGA 640 x 480	IBM* 8514/A 1024 x 768 EVGA 800 x 600 VGA 640 x 480	IBM* 8514/A 1024 x 768 Ni EVGA 800 x 600 VGA 640 x 480
Dot Pitch	0,28 mm	0,28 mm	0,28 mm
Input Video Signal	RGB Analogue	RGB Analogue	RGB Analogue
Horizontal Scan Frequency	31,5 / 36,16 / 35,52 KHz	31,5 / 36,16 / 35,52 KHz	31,5 / 36,16 / 35,52 / 48 KHz
Vertical Scan Frequency	50 / 60 / 70 / 87 Hz	50 / 60 / 70 / 87 Hz	50 / 60 / 70 / 87 Hz
Bandwidth	45 MHz	45 MHz	65 MHz
Power Consumption	84 Watt, 110/230 V Switch	84 Watt, 110/230 V Switch	75 Watt, 110/230 V Switch
Front Controls	Power Contrast Brightness	Power Contrast Brightness	Power Contrast Brightness
Rear Controls	H/V Size H/V Position	H/V Size H/V Position	H/V Size H/V Position
Dimensions (W x D x H mm)	350 x 370 x 352	350 x 370 x 352	357 x 398 x 385
Accessories	Tilt / Swivel Stand Power Cable User Manual	Tilt / Swivel stand Power Cable User Manual	Tilt/ Swivel stand Power Cable User Manual

*IBM

Registered trademark

All specifications subject to change without notice.

KAISER
THE SOFT WAY TO HARDWARE

KAISER nv/sa ~ Prins Karellaan 45 ~ B - 3090 OVERIJSE ~ Tel.: 02/ 688.01.20 (6 l.) ~ Fax: 02/688.03.43

<https://classic.technology>